

Blackout

Performance Data

Total Solar Energy Reduction	84%
Solar Energy Reflected	36%
Solar Energy Absorbed	63%
Solar Energy Transmittance	1%
Visible Light Transmittance	0%
Visible Light Reflected	17%
Ultra Violet Light Reflected	99%
Shading Coefficient	.19
Solar Heat Gain Coeff. (g Value)	
Emissivity	
Winter U-Factor (W/m ² °C)	
Glare Reduction	100%

Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	10 Years
Application	Internal

Key:

Excellent ☀️☀️☀️☀️☀️☀️ Some Benefit ☀️☀️☀️☀️☀️☀️
 N/A ☀️☀️☀️☀️☀️☀️



Window Film Description

A zero vision and virtually total opacity makes Blackout the absolute screening for privacy.

Available in various colours and shades.

10 year warranty against peeling, discolouration, bubbling and cracking.

Applications

Ideal for most internal and external glass applications including commercial, residential and industrial applications.