

Bronze 35

Performance Data

Total Solar Energy Reduction	66%
Solar Energy Reflected	41%
Solar Energy Absorbed	39%
Solar Energy Transmittance	20%
Visible Light Transmittance	35%
Visible Light Reflected	29%
Ultra Violet Light Reflected	99%
Shading Coefficient	.39
Solar Heat Gain Coeff. (g Value)	.34
Emissivity	.68
Winter U-Factor (W/m ² °C)	2.82
Glare Reduction	61%

Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	12 Years
Application	Internal

Key:

Excellent ☀️☀️☀️☀️☀️☀️ Some Benefit ☀️☀️☀️☀️☀️☀️
 N/A ☀️☀️☀️☀️☀️☀️



Window Film Description

This solar reflective metal sputtered window film offers very good solar heat and glare reduction, but allows the natural light to enter, for a luminous interior, while affording a comfortable and temperate environment.

This film from the outside view gives a light warm copper finish with a clear view looking out.

12 year warranty against peeling, discolouration, bubbling and cracking.

Applications

Ideal for most internal glass applications including commercial, residential and industrial applications. A popular film for schools, commercial buildings and residential buildings.