

Silver Shade

Performance Data

Total Solar Energy Reduction	70%
Solar Energy Reflected	40%
Solar Energy Absorbed	42%
Solar Energy Transmittance	18%
Visible Light Transmittance	22%
Visible Light Reflected	41%
Ultra Violet Light Reflected	99%
Shading Coefficient	.33
Glare Reduction	76%

Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	10 Years
Application	Internal

Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️ Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
 N/A ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️



Window Film Description

This film has been specially designed to be applied to the internal side of polycarbonate, GPR and plastic substrates. The film has a high performance metallised coating, offering a very low mirror appearance, which allows the natural light to enter the room

10 year warranty against peeling, discolouration, bubbling and cracking.

Applications

Ideal for polycarbonate and GRP materials for commercial, residential and industrial applications. A popular film for conservatory roofs.