

True Vue 40

Performance Data

Total Solar Energy Reduction	56%
Solar Energy Reflected	22%
Solar Energy Absorbed	46%
Solar Energy Transmittance	32%
Visible Light Transmittance	36%
Visible Light Reflected	22%
Ultra Violet Light Reflected	99%
Shading Coefficient	.63
Solar Heat Gain Coeff. (g Value)	.54
Emissivity	.75
Winter U-Factor (W/m ² °C)	2.72
Glare Reduction	56%



Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	12 Years
Application	Internal



Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️ Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
 N/A ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️

Window Film Description

A good solar reflective metal sputtered window film with a warm neutral low internal reflectance, but allows the natural light to enter, for a luminous interior, while affording a comfortable and temperate environment.

This film from the outside view gives a neutral charcoal finish with a low reflective clear internal view looking out.

12 year warranty against peeling, discolouration, bubbling and cracking.

Carbon Negative

Carbon Negative window film means that the environmental impact required to manufacture, distribute, install and dispose of at the end of the films life cycle, is less than the carbon reduction achieved as a result of the window films installation.

Applications

Ideal for most internal glass applications for heat, glare and UV protection on commercial, residential and industrial applications. A popular film for schools, commercial buildings, conservatory roof glass and daytime privacy.