

# Whiteout

## Performance Data

Total Solar Energy Reduction	70%
Solar Energy Reflected	40%
Solar Energy Absorbed	43%
Solar Energy Transmittance	17%
Visible Light Transmittance	13%
Visible Light Reflected	95%
Ultra Violet Light Reflected	99%
Shading Coefficient	.35
Solar Heat Gain Coeff. (g Value)	
Emissivity	.86
Winter U-Factor (W/m <sup>2</sup> °C)	
Glare Reduction	86%

## Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	10 Years
Application	Internal

Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️    Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️  
 N/A ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️



## Window Film Description

A zero vision and virtually total opacity makes Whiteout the absolute screening for privacy.

Available in various colours and shades.

10 year warranty against peeling, discolouration, bubbling and cracking.

## Applications

Ideal for most internal and external glass applications including commercial, residential and industrial applications.