

SL50 OSW

Performance Data

Total Solar Energy Reduction	57%
Solar Energy Reflected	21%
Solar Energy Absorbed	49%
Solar Energy Transmittance	48%
Visible Light Transmittance	48%
Visible Light Reflected	20%
Ultra Violet Light Reflected	99%
Shading Coefficient	.51
Solar Heat Gain Coeff. (g Value)	.43
Emissivity	
Winter U-Factor (W/m ² °C)	
Glare Reduction	45%

Performance Guide

Solar Heat Rejection	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Glare Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
UV Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Fade Reduction	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Safety & Security	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
One-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Two-Way Privacy	☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
Scratch Resistance Coating	Yes
Warranty Period	7 Years Vertical
Application	External

Key:

Excellent ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️ Some Benefit ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️
 N/A ☀️☀️☀️☀️☀️☀️☀️☀️☀️☀️



Window Film Description

This is a virtually invisible window film, designed to block select wavelengths of infrared and visible light radiation keeping the sun's harmful heat and glare out, but allowing the natural light to enter, for a luminous interior, while affording a comfortable and temperate environment.

This film is virtually undetectable once applied making it ideal for retail, historic, domestic and any building where a clear view is required in and out through the glazing and not change the look of the windows.

7 year vertical glass and 5 year sloping glass warranty against peeling, discolouration, bubbling and cracking.

Applications

SL50 OSW is ideal for any glazing that requires a clear view in and out, day or night time and not change the appearance of a building. Suitable for external applications.